

OXIBOND 4002

ELSTOMERIC WHITE ACRYLIC WATERPROOFER WATERPROOFING RANGE



Description

OXIBOND 4002 is a white acrylic latex protective paint suitable to be applied on interior or exterior surfaces wherever extra protection & washable surfaces are needed, particularly in extreme temperatures and harsh weather conditions.

Recommended For

Recommended for extreme temperatures and harsh weather conditions.

Waterproofing of interior & exterior applications on plaster, gypsum board, concrete, cement rendering, brickwork, block work, etc.

Key Features

- Anti-carbonation properties
- Crack-bridging
- Water vapor permeable
- Water & humidity repellent
- Will stop the growth of mold & fungi

Physical Properties

Solvent Type	Waterborne
Finish Type	White eggshell luster on ASTM D523
Spreading Rate	Approximately 8 - 10 m ² / kg depending on surface porosity and application techniques
Average Dry Time	Touch-dry in 1 hour based on ASTM D 1640
Recoat	After 2 - 3 hours based on ASTM D1640 / Full cure 24 hours
Dry Film Thickness	Approximately 40 – 60 microns depending on application methods
Thinner	Clean water / Thin up to 25% max for the first coat / Thin up to 10% max for the following coats
Adhesion	Classified 4B based on ASTM 3359-B for excellent adhesion
Gloss	60° - 20
Density	1.08 g/cm ³
Solids	Approximately 40 %
Viscosity	4 000 – 8 000 cP (Spindle 3 / Speed 10)
VOC	Very low VOC content - Compliant with EU 2010 regulations maximum of 30 g/L.

Surface Preparation

All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or any other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean.

New plaster or masonry surfaces must be allowed to cure (28 days) before applying base coat. Cured plaster should be hard, have a slight sheen and a maximum pH of 10. A soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

CAUTION: Scraping or sanding surfaces of older buildings may release dust containing lead or asbestos. **EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH.** Always wear appropriate personal protective equipment during surface preparation and finish clean up of any residues by water-washing all surfaces.

COLORTEK®
Wall and Floor Fashion

info@colortek.eu
www.colortek.eu



OXIBOND 4002

ELSTOMERIC WHITE ACRYLIC WATERPROOFER WATERPROOFING RANGE



Application Conditions

Do not apply at temperatures below 5 °C or when rain is expected.

Application Method

Stir well. Apply using brush, roller or airless spray.

Pack Size

- 1 US Quart – 0.9 kg
- 1 US Gallon – 3.95 kg
- 1 US Drum – 17 kg

Shelf Life

24 months from the date of production.

Storage and Handling

Care should be taken to avoid spillage. Product should be stored in a dry area and protected from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.

Safety

Use under well ventilated conditions. Do not breathe or inhale spray mist or sanding dust. Avoid skin contact; spillage on the skin should immediately be removed with suitable cleanser, soap and water. In case of eye contact, flush immediately with water for at least 15 minutes and seek medical attention immediately. If you have trouble breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

Cleaning

Remove as much leftover product as possible from the application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Do not empty product into drains or watercourses.

Technical Assistance

Available through your local COLORTEK® Design Center or through your COLORTEK PAINTS® authorized distributor. For the location of the retailer nearest you, email us at info@colortek.eu or check our website www.colortek.eu.

Disclaimer

Product batches are subject to stringent quality control checks in conformity with ISO 9001:2008, Certificate CH12/1128.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted based on the information supplied herein.